



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 29

LOCTITE 3D PRO9274 GRAY

SDS No. : 821775

V001.0

Revision: 13.10.2023

printing date: 21.11.2023

Replaces version from: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 3D PRO9274 GRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

3D Printing Resin

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

4-(1,1-dimethylethyl)cyclohexyl acrylate

Dicyclopentylidimethylene diacrylate
 (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

Tris(2-acryloxyethyl) isocyanurate
 Epoxy Acrylate Oligomer
 Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

Triacrylate ester
 1,6-Hexanediol diacrylate
 2-Hydroxyethyl acrylate

Triphenyl phosphite

Signal word:

Danger

Hazard statement:

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statement:
Prevention**

P273 Avoid release to the environment.
 P280 Wear protective gloves/eye protection.
 P261 Avoid breathing vapors.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2 282-104-8	20- < 25 %	Skin Irrit. 2, H315 2, H319 STOT SE 3, H335 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	STOT SE 3; H335; C >= 10 % ===== M acute = 1	
Dicyclopentylidimethylene diacrylate 42594-17-2 255-901-3 01-2120051112-76	10- 20 %	Skin Sens. 1B, H317 Aquatic Chronic 2, H411		
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5 256-032-2 01-2119484613-34	10- 20 %	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	STOT SE 3; H335; C >= 10 %	
Tris(2-acryloxyethyl) isocyanurate 40220-08-4 254-843-6 01-2120741502-64	5- < 10 %	Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411		
Epoxy Acrylate Oligomer 55818-57-0 500-130-2 01-2119490020-53	5- < 10 %	Skin Sens. 1, H317 Aquatic Chronic 2, H411		
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7 282-810-6 01-2119987994-10	1- < 5 %	Aquatic Chronic 2, H411 Skin Sens. 1B, H317		
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9 272-697-1 01-2119379499-16	1- < 5 %	STOT RE 2, Inhalation, H373		
Triacrylate ester 52408-84-1 500-114-5 500-114-5 01-2119487948-12	0,1- < 1 %	Eye Irrit. 2, H319 Skin Sens. 1B, H317		
1,6-Hexanediol diacrylate 13048-33-4 235-921-9 01-2119484737-22	0,025- < 0,25 %	Aquatic Acute 1, H400 Aquatic Chronic 2, H411 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	M acute = 1	
Butyl hydroxytoluene 128-37-0 204-881-4 01-2119565113-46	0,025- < 0,25 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17	0,1- < 1 %	Carc. 2, Inhalation, H351		
2-Hydroxyethyl acrylate 818-61-1 212-454-9 01-2119459345-34	0,025- < 0,25 %	Acute Tox. 4, Oral, H302 Acute Tox. 3, Dermal, H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400	Skin Sens. 1; H317; C >= 0,2 % ===== M acute = 1	

		Aquatic Chronic 3, H412		
Triphenyl phosphite 101-02-0 202-908-4 01-2119511213-58	0,025- < 0,25 %	Acute Tox. 4, Oral, H302 Eye Irrit. 2, H319 Skin Irrit. 2, H315 STOT RE 2, H373 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	Skin Irrit. 2; H315; C >= 5 % Eye Irrit. 2; H319; C >= 5 % ===== dermal:ATE = 2.500 mg/kg	

**If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Redness, inflammation.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed.

Refer to Technical Data Sheet

7.3. Specific end use(s)

3D Printing Resin

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
2,6-di-tert-Butyl-p-cresol 128-37-0 [2,6-DI-TERT-BUTYL-P-CRESOL]		10	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
2,6-di-tert-Butyl-p-cresol 128-37-0 [2,6-DITERTIARY-BUTYL-PARA-CRESOL]		2	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		4	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
(Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2	aqua (freshwater)		0,0016 mg/l				
(Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2	aqua (marine water)		0,00016 mg/l				
(Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2	sediment (freshwater)				0,6576 mg/kg		
(Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2	sediment (marine water)				0,0658 mg/kg		
(Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2	Soil				0,1306 mg/kg		
(Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2	sewage treatment plant (STP)		10 mg/l				
(Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate 42594-17-2	aqua (intermittent releases)		0,016 mg/l				
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	aqua (freshwater)		0,005 mg/l				
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Freshwater - intermittent		0,046 mg/l				
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	aqua (marine water)		0 mg/l				
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	sewage treatment plant (STP)		10 mg/l				
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	sediment (freshwater)				0,487 mg/kg		
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	sediment (marine water)				0,049 mg/kg		
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Soil				0,095 mg/kg		
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacylate 40220-08-4	aqua (freshwater)		0,00943 mg/l				
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacylate 40220-08-4	aqua (intermittent releases)		0,0943 mg/l				
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacylate 40220-08-4	sewage treatment plant (STP)		10 mg/l				
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacylate 40220-08-4	aqua (marine water)		0,000943 mg/l				
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacylate 40220-08-4	sediment (freshwater)				0,62 mg/kg		
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacylate 40220-08-4	sediment (marine water)				0,062 mg/kg		
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacylate 40220-08-4	Soil				0,118 mg/kg		

4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	aqua (freshwater)		0,025 mg/l				
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	aqua (marine water)		0,003 mg/l				
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	sewage treatment plant (STP)		10 mg/l				
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	sediment (freshwater)				8,96 mg/kg		
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	sediment (marine water)				0,896 mg/kg		
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	Soil				1,78 mg/kg		
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	aqua (freshwater)		0,00101 mg/l				
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	aqua (marine water)		0,000101 mg/l				
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	aqua (intermittent releases)		0,035 mg/l				
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	sediment (freshwater)				0,24 mg/kg		
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	sediment (marine water)				0,024 mg/kg		
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	Soil				0,047 mg/kg		
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	aqua (freshwater)		0,006 mg/l				
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	aqua (intermittent releases)		0,057 mg/l				
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	Sewage treatment plant		10 mg/l				
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	sediment (freshwater)				0,078 mg/kg		
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	sediment (marine water)				0,008 mg/kg		
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	aqua (marine water)		0,001 mg/l				
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	Soil				0,012 mg/kg		
Hexamethylene diacrylate 13048-33-4	aqua (freshwater)		0,007 mg/l				
Hexamethylene diacrylate 13048-33-4	aqua (marine water)		0,001 mg/l				
Hexamethylene diacrylate 13048-33-4	Soil				0,094 mg/kg		
Hexamethylene diacrylate 13048-33-4	sewage treatment plant (STP)		2,7 mg/l				
Hexamethylene diacrylate 13048-33-4	sediment (freshwater)				0,493 mg/kg		
Hexamethylene diacrylate 13048-33-4	sediment (marine water)				0,049 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (freshwater)		0,000199 mg/l				
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (marine water)		0,00002 mg/l				
2,6-Di-tert-butyl-p-cresol 128-37-0	sewage treatment plant		0,17 mg/l				

	(STP)						
2,6-Di-tert-butyl-p-cresol 128-37-0	sediment (freshwater)				0,0996 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	sediment (marine water)				0,00996 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	Soil				0,04769 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	oral				8,33 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (intermittent releases)		0,00199 mg/l				
2,6-Di-tert-butyl-p-cresol 128-37-0	Air						no hazard identified
2-Hydroxyethyl acrylate 818-61-1	aqua (freshwater)		0,017 mg/l				
2-Hydroxyethyl acrylate 818-61-1	aqua (marine water)		0,002 mg/l				
2-Hydroxyethyl acrylate 818-61-1	aqua (intermittent releases)		0,036 mg/l				
2-Hydroxyethyl acrylate 818-61-1	sediment (freshwater)				0,064 mg/kg		
2-Hydroxyethyl acrylate 818-61-1	sediment (marine water)				0,006 mg/kg		
2-Hydroxyethyl acrylate 818-61-1	Soil				0,003 mg/kg		
2-Hydroxyethyl acrylate 818-61-1	Sewage treatment plant		10 mg/l				
2-Hydroxyethyl acrylate 818-61-1	Air						no hazard identified
Triphenyl phosphite 101-02-0	aqua (freshwater)		0,0077 mg/l				
Triphenyl phosphite 101-02-0	Sewage treatment plant		2,1 mg/l				
Triphenyl phosphite 101-02-0	Soil				0,136 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Workers	inhalation	Long term exposure - systemic effects		2,35 mg/m ³	
(1-Methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Workers	dermal	Long term exposure - systemic effects		1,7 mg/kg	
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triy)tri-2,1-ethanediyl triacrylate 40220-08-4	Workers	inhalation	Long term exposure - systemic effects		1,65 mg/m ³	
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triy)tri-2,1-ethanediyl triacrylate 40220-08-4	Workers	dermal	Long term exposure - systemic effects		2,3 mg/kg	
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triy)tri-2,1-ethanediyl triacrylate 40220-08-4	General population	inhalation	Long term exposure - systemic effects		0,29 mg/m ³	
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triy)tri-2,1-ethanediyl triacrylate 40220-08-4	General population	oral	Long term exposure - systemic effects		0,08 mg/kg	
(2,4,6-Trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triy)tri-2,1-ethanediyl triacrylate 40220-08-4	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	Workers	inhalation	Long term exposure - systemic effects		1,17 mg/m ³	
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	Workers	dermal	Long term exposure - systemic effects		33 mg/kg	
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	General population	inhalation	Long term exposure - systemic effects		0,29 mg/m ³	
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	General population	dermal	Long term exposure - systemic effects		16,67 mg/kg	
4,4'-isopropylidenediphenol-, polymer with (chloromethyl)oxirane, acrylate 55818-57-0	General population	oral	Long term exposure - systemic effects		0,17 mg/kg	
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	Workers	dermal	Long term exposure - systemic effects		1,7 mg/kg	
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	Workers	inhalation	Long term exposure - systemic effects		5,88 mg/m ³	
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m ³	
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	General population	dermal	Long term exposure - systemic effects		0,5 mg/kg	
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	Workers	inhalation	Long term exposure - systemic effects		7,4 mg/m ³	
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	Workers	dermal	Long term exposure - systemic effects		2,1 mg/kg	
Hexamethylene diacrylate 13048-33-4	Workers	dermal	Long term exposure - systemic effects		2,77 mg/kg	
Hexamethylene diacrylate 13048-33-4	Workers	inhalation	Long term exposure - systemic effects		24,48 mg/m ³	
Hexamethylene diacrylate 13048-33-4	General population	dermal	Long term exposure - systemic effects		1,66 mg/kg	

Hexamethylene diacrylate 13048-33-4	General population	inhalation	Long term exposure - systemic effects		7,24 mg/m3	
Hexamethylene diacrylate 13048-33-4	General population	oral	Long term exposure - systemic effects		2,08 mg/kg	
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	inhalation	Long term exposure - systemic effects		3,5 mg/m3	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	dermal	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	inhalation	Long term exposure - systemic effects		0,86 mg/m3	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	dermal	Long term exposure - systemic effects		0,25 mg/kg	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	oral	Long term exposure - systemic effects		0,25 mg/kg	no hazard identified
Titanium dioxide 13463-67-7	Workers	inhalation	Long term exposure - local effects		0,17 mg/m3	
Titanium dioxide 13463-67-7	General population	inhalation	Long term exposure - local effects		0,028 mg/m3	
2-Hydroxyethyl acrylate 818-61-1	Workers	inhalation	Long term exposure - local effects		2,4 mg/m3	no hazard identified
2-Hydroxyethyl acrylate 818-61-1	General population	inhalation	Long term exposure - local effects		1,2 mg/m3	no hazard identified
Triphenyl phosphite 101-02-0	General population	dermal	Long term exposure - systemic effects		0,150 mg/kg	
Triphenyl phosphite 101-02-0	General population	inhalation	Long term exposure - systemic effects		0,53 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	grey
Odor	Acrylic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	< 0 °C (< 32 °F)
Initial boiling point	> 149 °C (> 300.2 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	> 93,3 °C (> 199.94 °F)
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (40 °C (104 °F);)	> 20,5 mm ² /s
Viscosity, dynamic (; 20 °C (68 °F))	150 - 300 mPa.s
Solubility (qualitative) (40 °C (104 °F); Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (20 °C (68 °F))	Mixture < 13 hPa
Density (25 °C (77 °F))	1,0 - 1,1 g/ml
Relative vapour density: (20 °C)	Heavier than air
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.

Acids.

Reducing agents.

Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

Hydrocarbons

nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	LD50	5.000 mg/kg	rat	BASF Test
Dicyclopentyl dimethylene diacrylate 42594-17-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	LD0	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Epoxy Acrylate Oligomer 55818-57-0	LD0	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Epoxy Acrylate Oligomer 55818-57-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphite 84434-11-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Triacrylate ester 52408-84-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
1,6-Hexanediol diacrylate 13048-33-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Butyl hydroxytoluene 128-37-0	LD50	> 6.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
2-Hydroxyethyl acrylate 818-61-1	LD50	540 mg/kg	rat	not specified
Triphenyl phosphite 101-02-0	LD50	1.590 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Dicyclopentyl dimethylene diacrylate 42594-17-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Epoxy Acrylate Oligomer 55818-57-0	LD0	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Epoxy Acrylate Oligomer 55818-57-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	LD50	> 5.000 mg/kg	rabbit	not specified
Triacrylate ester 52408-84-1	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
1,6-Hexanediol diacrylate 13048-33-4	LD50	3.650 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Butyl hydroxytoluene 128-37-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Titanium dioxide 13463-67-7	LD50	> 10.000 mg/kg	rabbit	not specified
Triphenyl phosphite 101-02-0	LD50	> 2.000 - < 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Triphenyl phosphite 101-02-0	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	LC50	> 5,01 mg/l	dust/mist	4 h	rat	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method)
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
Triphenyl phosphite 101-02-0	LC50	> 6,7 mg/l	dust/mist	1 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Dicyclopentylidimethylene diacrylate 42594-17-2	not irritating		In vitro	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
(1-methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Epoxy Acrylate Oligomer 55818-57-0	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Triacrylate ester 52408-84-1	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,6-Hexanediol diacrylate 13048-33-4	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Butyl hydroxytoluene 128-37-0	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Dicyclopentylidimethylene diacrylate 42594-17-2	not irritating		In vitro	OECD Guideline 437 (BCOP)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	moderately irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Epoxy Acrylate Oligomer 55818-57-0	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Triacrylate ester 52408-84-1	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,6-Hexanediol diacrylate 13048-33-4	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Butyl hydroxytoluene 128-37-0	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Dicyclopentyl dimethylene diacrylate 42594-17-2	Sub-Category 1B (sensitising)	Freund's complete adjuvant test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
(1-methyl-1,2-ethanediyl)bis[oxymethyl-2,1-ethanediyl] diacrylate 42978-66-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Epoxy Acrylate Oligomer 55818-57-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Epoxy Acrylate Oligomer 55818-57-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphite 84434-11-7	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Triacrylate ester 52408-84-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
1,6-Hexanediol diacrylate 13048-33-4	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Butyl hydroxytoluene 128-37-0	not sensitising	Draize Test	guinea pig	Draize Test
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2-Hydroxyethyl acrylate 818-61-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified
Triphenyl phosphite 101-02-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Triphenyl phosphite 101-02-0	sensitising	Guinea pig maximisation test	guinea pig	EPA OPPTS 870.2600 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Dicyclopentyl dimethylene diacrylate 42594-17-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	negative	bacterial reverse mutation assay (e.g Ames test)			OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	negative	in vitro mammalian chromosome aberration test			OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	negative	mammalian cell gene mutation assay			OECD Guideline 490 (In Vitro Mammalian Cell Gene Mutation Tests Using the Thymidine Kinase Gene)
Triacrylate ester 52408-84-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Triacrylate ester 52408-84-1	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Triacrylate ester 52408-84-1	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,6-Hexanediol diacrylate 13048-33-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,6-Hexanediol diacrylate 13048-33-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butyl hydroxytoluene 128-37-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
Butyl hydroxytoluene 128-37-0	negative	in vitro mammalian chromosome aberration test	with and without		not specified
Butyl hydroxytoluene 128-37-0	negative	mammalian cell gene mutation assay	with		not specified
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
2-Hydroxyethyl acrylate 818-61-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Butyl hydroxytoluene 128-37-0		oral: feed	2 y daily	rat	male	
Titanium dioxide 13463-67-7	not carcinogenic	oral: feed	103 w daily	rat	male/female	not specified

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	NOAEL P 250 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Triacrylate ester 52408-84-1	NOAEL P 750 mg/kg NOAEL F1 >= 750 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
1,6-Hexanediol diacrylate 13048-33-4	NOAEL P 250 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butyl hydroxytoluene 128-37-0	NOAEL P 500 mg/kg	Two generation study	oral: feed	rat	not specified
Titanium dioxide 13463-67-7	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	one-generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Dicyclopentylidimethylene diacrylate 42594-17-2	NOAEL 1.000 mg/kg	oral: gavage		rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
(1-methyl-1,2- ethanediyl)bis[oxy(methyl -2,1-ethanediyl)] diacrylate 42978-66-5	NOAEL 250 mg/kg	oral: gavage	28 - 52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOAEL 491,5 mg/kg	oral: feed	6 months daily	rat	not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOAEL 0,01 mg/kg	inhalation: dust	12 months 6 h/d, 5 d/wk	rat	not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOAEL 0,01 mg/kg	inhalation: dust	12 months 6 h/d, 5 d/wk	monkey	not specified
Triacrylate ester 52408-84-1	NOAEL 250 mg/kg	oral: gavage	28-52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
1,6-Hexanediol diacrylate 13048-33-4	NOAEL 250 mg/kg	oral: gavage	28 - 52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butyl hydroxytoluene 128-37-0	NOAEL 25 mg/kg	oral: feed	daily	rat	not specified
Titanium dioxide 13463-67-7	NOAEL > 1.000 mg/kg	oral: gavage	92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Triphenyl phosphite 101-02-0	NOAEL 15 mg/kg	oral: gavage	16 weeks daily	rat	equivalent or similar to OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reprod./Develop. Tox. Screening Test)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	LC50	> 1 - 10 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Dicyclopentylidimethylene diacrylate 42594-17-2	LC50	1,65 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	LC50	> 4,5 - 10 mg/l	96 h	Leuciscus idus	DIN 38412-15
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	LC50	9,43 mg/l	96 h	Danio rerio (reported as Brachydanio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Epoxy Acrylate Oligomer 55818-57-0	LL50	> 100 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Epoxy Acrylate Oligomer 55818-57-0	NOEC	0,25 mg/l	33 d	Pimephales promelas	OECD Guideline 210 (fish early lite stage toxicity test)
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	LC50	1,89 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	LC50	> 10.000 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Triacrylate ester 52408-84-1	LC50	5,74 mg/l	96 h	Danio rerio (reported as Brachydanio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,6-Hexanediol diacrylate 13048-33-4	LC50	0,38 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,6-Hexanediol diacrylate 13048-33-4	NOEC	0,072 mg/l	39 d	Oryzias latipes	OECD Guideline 210 (fish early lite stage toxicity test)
Butyl hydroxytoluene 128-37-0	LC50	Toxicity > Water solubility	96 h	Brachydanio rerio (new name: Danio rerio)	EU Method C.1 (Acute Toxicity for Fish)
Butyl hydroxytoluene 128-37-0	NOEC	0,053 mg/l	30 d	Oryzias latipes	OECD Guideline 210 (fish early lite stage toxicity test)
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxyethyl acrylate 818-61-1	LC50	4,8 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Triphenyl phosphite 101-02-0	LC50	> 16 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	EC50	1,03 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Dicyclopentylidimethylene diacrylate 42594-17-2	EC50	2,36 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
(1-methyl-1,2-	EC50	88,7 mg/l	48 h	Daphnia magna	OECD Guideline 202

ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5					(Daphnia sp. Acute Immobilisation Test)
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	EC50	158,3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Epoxy Acrylate Oligomer 55818-57-0	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	EC50	2,26 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	EC50	> 1.000 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Triacrylate ester 52408-84-1	EC50	91,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,6-Hexanediol diacrylate 13048-33-4	EC50	2,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butyl hydroxytoluene 128-37-0	EC50	0,48 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Hydroxyethyl acrylate 818-61-1	EC50	9,3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Triphenyl phosphite 101-02-0	EC50	> 1 - 5 mg/l	48 h	Daphnia sp.	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Epoxy Acrylate Oligomer 55818-57-0	NOEC	>= 0,51 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOEC	132,7 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
1,6-Hexanediol diacrylate 13048-33-4	NOEC	0,14 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Butyl hydroxytoluene 128-37-0	NOEC	0,069 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)
2-Hydroxyethyl acrylate 818-61-1	NOEC	0,86 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	EC50	0,539 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	EC10	0,414 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dicyclopentyl dimethylene diacrylate 42594-17-2	EC50	1,6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dicyclopentyl dimethylene diacrylate 42594-17-2	EC10	0,64 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
(1-methyl-1,2-ethanediyl)bis[oxymethyl-2,1-ethanediyl] diacrylate 42978-66-5	EC50	28 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	EC50	25,7 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	EC10	12,9 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Epoxy Acrylate Oligomer 55818-57-0	EC50	105 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Epoxy Acrylate Oligomer 55818-57-0	NOEC	1,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	EC50	1,01 mg/l	72 h	Desmodesmus subspicatus	not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	EC50	> 173,1 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOEC	173,1 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triacrylate ester 52408-84-1	EC50	12,2 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triacrylate ester 52408-84-1	EC10	2,06 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,6-Hexanediol diacrylate 13048-33-4	EC50	2,33 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,6-Hexanediol diacrylate 13048-33-4	NOEC	0,9 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butyl hydroxytoluene 128-37-0	EC50	Toxicity > Water solubility	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Butyl hydroxytoluene 128-37-0	EC10	0,4 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl acrylate 818-61-1	EC50	6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl acrylate 818-61-1	NOEC	1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	EC10	490 mg/l	3 h	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate 42978-66-5	EC 50	> 10.000 mg/l	30 min		not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	EC50	> 2.500 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Triacrylate ester 52408-84-1	EC20	507 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
1,6-Hexanediol diacrylate 13048-33-4	EC20	60 mg/l	30 min	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Butyl hydroxytoluene 128-37-0	EC50	Toxicity > Water solubility	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
2-Hydroxyethyl acrylate 818-61-1	EC10	> 100 mg/l	72 h	activated sludge, domestic	other guideline:
Triphenyl phosphite 101-02-0	EC 50	> 100 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	not readily biodegradable.	aerobic	4 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Dicyclopentylidimethylene diacrylate 42594-17-2	not readily biodegradable.	aerobic	28 %	28 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	not readily biodegradable.	aerobic	48 %	28 d	EU Method C.4-C (Determination of the "Ready" Biodegradability: Carbon Dioxide Evolution Test)
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	not readily biodegradable.	aerobic	14,5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Epoxy Acrylate Oligomer 55818-57-0	not readily biodegradable.	aerobic	42 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7		aerobic	< 10 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Triacrylate ester 52408-84-1	readily biodegradable	aerobic	72 - 85 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,6-Hexanediol diacrylate 13048-33-4	readily biodegradable	aerobic	69 %	28 d	OECD Guideline 310 (Ready Biodegradability: CO2 in Sealed Vessels (Headspace Test))
1,6-Hexanediol diacrylate 13048-33-4	inherently biodegradable	aerobic	> 70 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Butyl hydroxytoluene 128-37-0	not readily biodegradable.	aerobic	4,5 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Butyl hydroxytoluene 128-37-0	not inherently biodegradable	aerobic	5,2 - 5,6 %	35 d	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
2-Hydroxyethyl acrylate 818-61-1	readily biodegradable	aerobic	> 79 - 80 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Triphenyl phosphite 101-02-0	readily biodegradable	aerobic	84 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Butyl hydroxytoluene 128-37-0	330 - 1.800	56 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
4-(1,1-dimethylethyl)cyclohexyl acrylate 84100-23-2	5,6	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Dicyclopentylidimethylene diacrylate 42594-17-2	4,6		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	< 4		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	1,85	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Epoxy Acrylate Oligomer 55818-57-0	1,6 - 3,8	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	2,91	25 °C	EU Method A.8 (Partition Coefficient)
1,6-Hexanediol diacrylate 13048-33-4	2,81	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Butyl hydroxytoluene 128-37-0	5,1		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2-Hydroxyethyl acrylate 818-61-1	-0,17	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Triphenyl phosphite 101-02-0	6,62	25 °C	QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Dicyclopentylidimethylene diacrylate 42594-17-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 42978-66-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Epoxy Acrylate Oligomer 55818-57-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Triacrylate ester 52408-84-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1,6-Hexanediol diacrylate 13048-33-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Butyl hydroxytoluene 128-37-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Titanium dioxide 13463-67-7	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.
2-Hydroxyethyl acrylate 818-61-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Triphenyl phosphite 101-02-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-(1,1-Dimethylethyl)cyclohexyl acrylate,Dicyclopentyl dimethylene diacrylate)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-(1,1-Dimethylethyl)cyclohexyl acrylate,Dicyclopentyl dimethylene diacrylate)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-(1,1-Dimethylethyl)cyclohexyl acrylate,Dicyclopentyl dimethylene diacrylate)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-(1,1-Dimethylethyl)cyclohexyl acrylate,Dicyclopentyl dimethylene diacrylate)
IATA	Environmentally hazardous substance, liquid, n.o.s. (4-(1,1-Dimethylethyl)cyclohexyl acrylate,Dicyclopentyl dimethylene diacrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous

ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	Environmentally Hazardous

14.6. Special precautions for user

ADR	not applicable
	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.