Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD

Page 1 / 14



SAFETY DATA SHEET

SECTION 1 Identification of the substance/mixture and of the company/undertaking

1.1 / Product Identfier

POC Lab. - UV Resin Rubber-Like ESD

1.2 / Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Photoinitiator / For use with an LCD /MSLA/ DLP 3D printer

1.3 / Details of the supplier of the safety data sheet

POC Lab. Company: E.Mail: contact@poclab.xyz

320, rue Saint-Honoré 75001 - PARIS (France) Website: www.poclab.xyz

1.4 / Emergency telephone number

Number ORFILA (INRS): +33 (0)1 45 42 59 59 International emergency number: +49 180 2273-112

SECTION 2 Hazards Identification

2.1 / Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 (CLP)

Acute Tox. 4 (par voie orale) H302 Harmful if swallowed Skin Corr./Irrit. 2 H315 Causes skin irritation

Skin Sens. 1B H317 May cause an allergic skin reaction

Eye Dam./Irrit. 1 H319 Causes serious eye irritation

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD

Page 2 / 14

Aquatic Chronic 2

H411 Toxic to aquatic life with long lasting effects

For the classifications not written out in full in this section the full text can be found in section 16.

2.2 / Label elements

Globally Harmonized System, EU (GHS)

Pictogram:





Signal Word: Danger

- H302 Harmful if swallowed
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H411 Toxic to aquatic life with long lasting effects

Precautionary Statements (Prevention):

- P261 Avoid breathing dust/fume/gas/mist/vapours/ spray
- P264 Wash arms, hands and face thoroughly after handling
- P272 Contaminated work clothing should not be allowed out of the workplace
- P273 Avoid release to the environnement
- P280 Wear protective gloves/ protective clothing/eye protection/face protection

Precautionary Statements (Response):

- P305&P351&P338 IF IN EYE: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
- P302&352 IF ON SKIN: Wash with soap and water
- P310 Immediately call a POISON CENTER or doctor/physician

Precautionary Statements (Disposal):

 P501 Dospose of conttents and container in accordance with all local, regional, national and international regulations

According to Regulation (EC) No 1272/2008 (CLP)

Hazard determining component(s) for labelling:

Urethane acrylate oligomer / 2-[4-(2-{4-[2-(prop-2-enoyloxy)ethoxy]phenyl}propan-2-yl)phenoxy]ethyl prop-2-enoate / 2,4,6-tri-tert-butylphénol / SWCNT / 2,2'-ethylenedioxydiethyl dimethacrylate / Alkylolammonium salt / Color pigment

2.3 / Other dangers

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD

Page 3 / 14

According to Regulation (EC) No 1272/2008 (CLP)

No particular dangers known, if the regulations/notes for storage and handling are observed.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3 Composition/information on ingredients

3.1 / Substances

Not applicable

3.2 / Mixtures

Chemical nature:

Preparation based on: Urethane acrylate oligomer / 2-[4-(2-{4-[2-(prop-2-enoyloxy)ethoxy]phenyl}propan-2-yl)phenoxy]ethyl prop-2-enoate / 2,4,6-tri-tert-butylphénol / SWCNT / 2,2'-ethylenedioxydiethyl dimethacrylate / Alkylolammonium salt / Color pigment

Hazardous ingredients (GHS):

- EC N° 944-664-8
 - Urethane acrylate oligomer
 - ∘ %W ≤ 65
 - Skin Irrit. 2 / Eye Irrit. 2
 - o H319, H315
- EC N° 613-584-2
 - 2-[4-(2-{4-[2-(prop-2-enoyloxy)ethoxy]phenyl}propan-2-yl)phenoxy]ethyl prop-2-enoate
 - Hexamethylene diacrylate
 - ∘ %W ≤ 40
 - Skin Irrit. 2 / Eye Irrit. 2 / Skin Sens. 1 / Aquatic Chronic 2 / STOT SE 3
 - H315, H319, H317, H411, H335
- EC N° 204-337-6
 - 2,4,6-tri-tert-butylphénol
 - %W < 1
 - Acute Tox. 4 / Eye Irrit. 2 / Acute Tox. 4 / Acute Tox. 2 / Skin Irrit. 2 / Eye Irrit. 2 / Skin Irrit. 2 / Stin Irrit. 2 / Stin Irrit. 2 / Stin Irrit. 2 / Skin I
 - H302, H319, H332, H330, H315, H335, H350, H411
- EC N° 952-189-2
 - o SWCNT
 - %W < 1
 - Eye Irrit. 2
 - H319
- EC N° 203-652-6
 - o 2,2'-ethylenedioxydiethyl dimethacrylate

Date / Révision : 2023/09/05 Rev. 1.0

Product : POC Lab. UV Resin Rubber-Like ESD

∘ %W < 2

- Skin Sens. 1 / Skin Sens. 1B / Skin Irrit. 2 / Eye Irrit. 2 / Resp. Sens. 1 / STOT SE 3
- H317, H315, H319, H334, H335
- EC N° 812-737-2
 - Alkylolammonium salt
 - ∘ %W < 1
 - Skin Irrit. 2 / Eye Irrit. 2 / Aquatic Acute 1 / Aquatic Chronic 1 / Aquatic Chronic 2
 - H315, H319, H400, H410, H411

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4 First aid measures

4.1 / Description first aid measures

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2 / Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far.

4.3 / Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5 Fire fighting measures

5.1 / Extingishing media:

Suitable extinguishing media: water spray, dry powder, foam

Page 4 / 14

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD Page 5 / 14

Unsuitable extinguishing media for safety reasons: water jet.

5.2 / Special hazards arising from the substance or mixture

harmful vapours:

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

5.3 / Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6 Accidental releases measures

6.1 / Personal precautions, protective equipment and emergency

Use personal protective clothing. Breathing protection required.

6.2 / Environmental precautions cautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

6.3 / Methods and material for containment and cleaning up

For large amounts:

Pump off product.

For residues:

Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

6.4 / Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7 Handling and storage

7.1 / Precautions for safe handling

No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD

Page 6 / 14

Heated containers should be cooled to prevent polymerization. Take precautionary measures against static discharges.

7.2 / Conditions for safe storage, including any incompatibilities

The product in undamaged packing need not be stored separately.

Further information on storage conditions: Protect against heat. Protect from the effects of light. The stabilizer is only effective in the presence of oxygen.

Handle and open containers with care. Close container tightly after use.

Protect from temperatures below: 15 °C

Protect from temperatures above: 35 °C

7.3 / Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8 Exposure Controls/Personal Protection

8.1 / Control parameters

Exposure parameters to be checked in the workplace

No known occupational exposure limit value.

8.2 / Exposure controls

Personal protective equipment

Respiratory protection:

Suitable respiratory protection for higher concentrations or long-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Protection des mains :

Gants de protection résistant aux produits chimiques (EN 374)

Hand protection:

Chemical resistant protective gloves (EN 374)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): nitrile rubber (NBR) - 0.4 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD Page 7 / 14

observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Respect the precautionary measures usually applicable when using chemicals. In addition to the indications on personal protective equipment, the wearing of closed work clothes is necessary.

SECTION 9 Physical and chemical properties

9.1 / Information on basic physical and chemical properties

Form: LiquideColor: Black

Odour: Type acrylique

Odour threshold: Not determinedpH value: Not determined

Melting point: Not determinedBoiling point: Not determined

Flash point: > 110 °C

Evaporation rate: Not determinedFlammability: Not determined

Lower explosion limit.: Not determined

Upper explosion limit.: Not determined

Ignition temperature: Not determinedVapour pressure: Not determined

Density: ≈ 1.15 g/cm3 (25 °C)

• Relative density: 1.15 (25 °C)

• Relatice vapour density (air): Not determined

Water Solubility: Insoluble

- Solubility (qualitative) solvent(s): Soluble in ethanol, ethyl acetate, benzene and other organic solvents
- Partitioning coefficient n-octanol/water (log Kow): not applicable for mixtures

Self ignition: Not self-igniting

Thermal decomposition: Not determined

Viscosity, dynamilc: ≈ 600 mPa.s (25 °C)

Explostion hazard: Not explosive

Fire promoting properties: Not fire-propagating

9.2 / Other information

- Surface tension: No data available
- Particle size distribution: The substance/product is marketed or used in non-solid form.

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD

Page 8 / 14

SECTION 10 Stability and reactivity

10.1 / Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2 /Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3 / Possibilty of hazardous reactions

The product may polymerize after significantly exceeding the allowable storage time or temperature. Heat release during polymerization. Reactions with peroxides and with other radical components. Strong exposure to light can cause a chemical reaction and generate strong heat.

Before delivery the product is stabilized to avoid spontaneous polymerization.

10.4 / Conditions to avoid

See SDS section 7 - Handling and storage.

10.5 / Incompatible materials

Materials to avoid: Oxidizing acid, alkali and water

10.6 / Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11 Toxicological Information

11.1 / Information on toxicological effects

Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after single ingestion.

Irritation

Skin Corrosion/Irritation: Irritant.

Serious eye damage/irritation: May cause severe irritation.

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD

Page 9 / 14

Respiratory/Skin sansitization

Assessment of sensitizing effect: Possible allergy, skin irritation after contact. No known significant effects or critical hazards.

Carcinogenicity

Assessment of carcinogenicity: The available information does not give any indication of a possible carcinogenic effect.

Reproductive toxicity

Reproductive Toxicity Assessment: No known significant effects or critical hazards

Developmental toxicity

Teratogenicity Assessment: Based on the components, no teratogenic effects are suspected.

Specific target organ toxicity (single exposure)

Simple Assessment of Specific Target Organ Toxicity (STOT): Based on available information, no specific target organ toxicity is anticipated from a single exposure.

Note: The product has not been tested. The indication given is derived from substances/products with a similar structure or composition.

Repeated Dose Toxicity and Specific Target Organ Toxicity (Repeated Exposure)

Assessment of repeated dose toxicity: The substance may cause specific damage to organs through repeated oral exposure.

Aspiration hazard

No aspiration hazard expected.

Other relevant toxicity information

.**-**

SECTION 12 Ecological Information

12.1 /Toxicity

Assessment of aquatic toxicity:

Harmful (acutely harmful) to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Product has not been tested. The indication is derived from the properties of individual components.

Fish Toxicity:

No data available.

Aquatic Invertebrates:

No data available.

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD

Page 10 / 14

Aquatic plants:

No data available.

Microorganisms/Effect on Activated Sludge:

No data available.

Chronic effects on fish:

No data available.

Chronic effects on aquatic invertebrates. :

No data available.

Terrestrial Toxicity Assessment:

No data available.

12.2 / Persistence and degradability

Assessment of biodegradability and elimination (H2O): Hardly biodegradable.

12.3 / Bioaccumulative potential

Assessment bioaccumulation potential:

The product has not been tested.

12.4 / Mobility in soil

Assessment transport between environmental compartments:

Volatility: No data available.

12.5 / Results of PBT and vPvB assessment

PBT and vPvB assessment:

The product does not contain any substance fulfilling the PBT criterion (Persistent/bioaccumulative/toxic) or the vPvB criterion (very Persistent and very bioaccumulative).

12.6 / Other adverse effects

The product does not contain substances listed in Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

12.7 / Additional information

Other Distribution and Residue Notes:

The treatment, or even the introduction of wastewater into a biological treatment plant must be carried out in compliance with local and regulatory requirements.

Other ecotoxicity information:

Harmful (acutely harmful) to aquatic organisms.

Date / Révision : 2023/09/05 Rev. 1.0

Product : POC Lab. UV Resin Rubber-Like ESD Page 11 / 14

SECTION 13 Disposal Considerations

13.1 / Waste treatment methods

Must be directed to an approved landfill or incinerated in an approved center while respecting local regulatory requirements.

Uncleaned packaging:

Uncontaminated packaging can be reused. Packaging that cannot be cleaned must be disposed of like the product it contained.

SECTION14 Transport information

Land transport

ADR - Non-hazardous product within the meaning of transport regulations

UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

RID - Non-hazardous product within the meaning of transport regulations

UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport fluvial intérieur

ADN - Non-hazardous product within the meaning of transport regulations

UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport maritime

IMDG - Non-hazardous product within the meaning of transport regulations

UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD

Page 12 / 14

Packing group:

Environmental hazards:

Special precautions for user:

Not applicable

None known

Transport aérien

IATA/ICAO - Non-hazardous product within the meaning of transport regulations

UN number:
UN proper shipping name:
Not applicable
Transport hazard class(es):
Packing group:
Not applicable
Environmental hazards:
Special precautions for user:
Not applicable
Not applicable
Not applicable
None known

14.1 / UN number

See corresponding entries for "UN number" for the respective regulations in the tables above.

14.2 / UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3 / Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4 / Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5 / Environmental hazards

14.6 / Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7 / Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:
Shipment approved:
Pollution name:
Pollution category:
Not evaluated

Date / Révision : 2023/09/05 Rev. 1.0

Product : POC Lab. UV Resin Rubber-Like ESD Page 13 / 14

SECTION 15 Regulatory information

15.1 / Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3

Directive 2012/18/EU - Control of major accident hazards involving dangerous substances (EU): Listed in the regulations above: no

15.2 / Chemical Safety Assessment

Advice on handling the product can be found in sections 7 and 8 of this safety data sheet.

SECTION 16 Other information

Any other intended applications should be discussed with the manufacturer.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox. Acute toxity

Skin Corr./Irrit. Skin corrosion/irritation

Eye Dam./Irrit. Serious eye damage/eye irritation

Skin Sens. Skin sensitization

STOT RE Specific target organ toxicity - repeated exposure
Aquatic Chronic Hazardous to the aquatic environnement - chronic
STOT SE Specific target organ toxicity - single exposure

Repr. Reproductive toxicity

Aquatic Acute Hazardous to the aquatic environnement - acute

H302 Harmful if swallowed
H315 Causes skin irritation

H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H335 May cause respiratory irritation

H411 Toxic to aquatic life with long lasting effects

Abbreviations

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road ADN = European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CLP = Regulation relating to classification, labeling and packaging of substances and mixtures

EC = European Community

EN = European standards

IATA = International Air Transport Association

IBC: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

Date / Révision : 2023/09/05 Rev. 1.0

Product: POC Lab. UV Resin Rubber-Like ESD

Page 14 / 14

IMDG = International Maritime Dangerous Goods Code
ISO = International Organization for Standardization
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
PBT = Persistent, Bioaccumulative and Toxic
RID = Regulations concerning the international carriage of dangerous goods by rail
UN number = UN number for the transport of dangerous goods
vPvB = very persistent and very bioaccumulative.

The data contained in this safety data sheet is based on our current experience and knowledge; they describe the product in terms of safety requirements. This safety data sheet is neither a certificate of analysis nor a technical data sheet and can in no way be considered as an agreement on our sales specifications. The uses identified in this safety data sheet represent neither an agreement on the corresponding contractual quality of the substance / mixture nor a contractually designated use. It is the responsibility of the purchaser of our products to ensure that all intellectual property rights and all applicable legislation are observed.