

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 27

LOCTITE 3D IND403 HDT80 High Modulus Black

SDS No. : 686093 V005.0 Revision: 17.04.2023 printing date: 19.05.2023 Replaces version from: 24.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 3D IND403 HDT80 High Modulus Black

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: 3D Printing Resin

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):	
Skin irritation	Category 2
H315 Causes skin irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate
	Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide
	2-Propenoic acid, 2-methyl-, 2-(2-hydroxyethoxy)ethyl ester
	Triacrylate ester
	Reaction mass of pentamethyl-4-piperidylsebacates Ethylene dimethacrylate
	Isobornyl acrylate
Signal word:	Warning
Hazard statement:	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.
	H411 Toxic to aquatic life with long lasting effects.
Precautionary statement:	P273 Avoid release to the environment.
Prevention	P280 Wear protective gloves.
Precautionary statement:	P302+P352 IF ON SKIN: Wash with plenty of soap and water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.
	1 337 11 515 Il Cyc Intution persists. Get medical advice/attention.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	Concentration	Classification	Specific Conc. Limits, M-	Add.
CAS-No. EC Number REACH-Reg No.			factors and ATEs	Information
2-Hydroxyethyl methacrylate 868-77-9 212-782-2 01-2119490169-29	25- 50 %	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319		
7,7,9(or 7,9,9)-trimethyl-4,13- dioxo-3,14-dioxa-5,12- diazahexadecane-1,16-diyl bismethacrylate 72869-86-4 276-957-5 01-2120751202-68	20- 40 %	Skin Sens. 1B, H317 Aquatic Chronic 2, H411		
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7 423-340-5 01-2119489401-38 01-2119936813-33	1- < 5%	Skin Sens. 1A, H317 Aquatic Chronic 4, H413		
2-Propenoic acid, 2-methyl-, 2- (2-hydroxyethoxy)ethyl ester 2351-43-1	1- < 5 %	Eye Irrit. 2, H319 Skin Sens. 1, H317		
Triacrylate ester 52408-84-1 500-114-5 500-114-5 01-2119487948-12	0,1-< 1 %	Eye Irrit. 2, H319 Skin Sens. 1B, H317		
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5 915-687-0 01-2119491304-40	0,1-< 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Repr. 2, H361f	M acute = 1 M chronic = 1 ===== dermal:ATE = 3.171 mg/kg	
Butyl hydroxytoluene 128-37-0 204-881-4 01-2119565113-46	0,1-< 0,25 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
methacrylic acid 79-41-4 201-204-4 01-2119463884-26	0,1-< 1 %	Acute Tox. 4, Oral, H302 Acute Tox. 3, Dermal, H311 Acute Tox. 4, Inhalation, H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	STOT SE 3; H335; C >= 1 % ===== dermal:ATE = 500 mg/kg inhalation:ATE = 3,61 mg/l;dust/mist	
Ethylene dimethacrylate 97-90-5 202-617-2	0,1-< 1 %	STOT SE 3, H335 Skin Sens. 1, H317 Aquatic Chronic 3, H412	STOT SE 3; H335; C >= 10 %	
Isobornyl acrylate 5888-33-5 227-561-6 01-2119957862-25	0,01-< 0,1 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear protective equipment. Ensure adequate ventilation. Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed. Refer to Technical Data Sheet

7.3. Specific end use(s)

3D Printing Resin

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ррт	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
2,6-di-tert-Butyl-p-cresol 128-37-0 [2,6-DI-TERT-BUTYL-P-CRESOL]		10	Time Weighted Average (TWA):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	72	Time Weighted Average (TWA):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	143	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
2,6-di-tert-Butyl-p-cresol 128-37-0 [2,6-DITERTIARY-BUTYL-PARA- CRESOL]		2	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	70	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	140	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
	put thicht	r	mg/l	ppm	mg/kg	others	
2-Hydroxyethyl methacrylate	aqua		0,482 mg/l				
868-77-9 2-Hydroxyethyl methacrylate	(freshwater)		0.482 mg/l				
868-77-9	aqua (marine water)		0,482 mg/l				
2-Hydroxyethyl methacrylate	sewage		10 mg/l				
868-77-9	treatment plant (STP)		10 mg/1				
2-Hydroxyethyl methacrylate	aqua		1 mg/l				
868-77-9	(intermittent releases)						
2-Hydroxyethyl methacrylate 868-77-9	sediment (freshwater)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	sediment (marine water)				3,79 mg/kg		
2-Hydroxyethyl methacrylate	Soil				0,476		
868-77-9 2-Hydroxyethyl methacrylate	Predator				mg/kg		no potential for
868-77-9							bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Marine water - intermittent		1 mg/l				
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-	aqua		0,01 mg/l				
dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	(freshwater)						
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-	aqua		0,1 mg/l	<u> </u>			
dioxa-5,12-diazahexadecane-1,16-diyl	(intermittent		.,				
bismethacrylate 72869-86-4	releases)						
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-	aqua (marine		0,001 mg/l				
dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	water)						
72869-86-4							
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-	sewage		3,61 mg/l				
dioxa-5,12-diazahexadecane-1,16-diyl	treatment plant						
bismethacrylate 72869-86-4	(STP)						
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-	sediment				4,56 mg/kg		
dioxa-5,12-diazahexadecane-1,16-diyl	(freshwater)				.,		
bismethacrylate 72869-86-4							
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-	sediment				0,46 mg/kg		
dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	(marine water)						
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-	Soil				0,91 mg/kg		
dioxa-5,12-diazahexadecane-1,16-diyl	Don				0,91 mg ng		
bismethacrylate 72869-86-4							
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-	Predator		1				no potential for
dioxa-5,12-diazahexadecane-1,16-diyl	1						bioaccumulation
bismethacrylate							
72869-86-4 Phenyl bis(2,4,6-trimethylbenzoyl)-	aqua		0,001 mg/l				
phosphine oxide	(freshwater)		0,001 mg/1				
162881-26-7							
Phenyl bis(2,4,6-trimethylbenzoyl)-	aqua		0,001 mg/l				
phosphine oxide	(intermittent						
162881-26-7 Phenyl bis(2,4,6-trimethylbenzoyl)-	releases) aqua (marine		0,001 mg/l	<u> </u>			
phosphine oxide	water)		0,001 mg/1				
162881-26-7							
Phenyl bis(2,4,6-trimethylbenzoyl)-	sewage		1 mg/l				
phosphine oxide	treatment plant						
162881-26-7 Phenyl bis(2,4,6-trimethylbenzoyl)-	(STP) sediment		+		0,712		
phosphine oxide	(freshwater)				0,712 mg/kg		
162881-26-7	(iresitwater)				····6/ **6		
Phenyl bis(2,4,6-trimethylbenzoyl)-	sediment				0,712		
phosphine oxide	(marine water)				mg/kg		
162881-26-7				1			

	1	1 1		
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide	Soil		20 mg/kg	
162881-26-7				
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO	aqua (freshwater)	0,006 mg/l		
52408-84-1	(iresitwater)			
Glycerol, propoxylated, esters with acrylic	aqua	0,057 mg/l		
acid 1-6.5PO 52408-84-1	(intermittent releases)			
Glycerol, propoxylated, esters with acrylic	Sewage	10 mg/l		
acid 1-6.5PO	treatment plant	Ũ		
52408-84-1	1. (0.079	
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO	sediment (freshwater)		0,078 mg/kg	
52408-84-1	(iresitwater)		111 <i>2</i> / 122	
Glycerol, propoxylated, esters with acrylic	sediment		0,008	
acid 1-6.5PO 52408-84-1	(marine water)		mg/kg	
Glycerol, propoxylated, esters with acrylic	aqua (marine	0,001 mg/l		
acid 1-6.5PO	water)	e, e e		
52408-84-1	0.1		0.012	
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO	Soil		0,012 mg/kg	
52408-84-1			iiig/kg	
Reaction mass of pentamethyl-4-	aqua	0,002 mg/l		
piperidylsebacates	(freshwater)			
1065336-91-5 Reaction mass of pentamethyl-4-	aqua (marine	0,00022		
piperidylsebacates	water)	mg/l		
1065336-91-5	· · · · · · · · · · · · · · · · · · ·	-		
Reaction mass of pentamethyl-4-	aqua	0,009 mg/l		
piperidylsebacates 1065336-91-5	(intermittent releases)			
Reaction mass of pentamethyl-4-	sewage	1 mg/l		
piperidylsebacates	treatment plant	-		
1065336-91-5 Reaction mass of pentamethyl-4-	(STP) sediment		1.05 mg/kg	
piperidylsebacates	(freshwater)		1,05 mg/kg	
1065336-91-5	()			
Reaction mass of pentamethyl-4-	sediment		0,11 mg/kg	
piperidylsebacates 1065336-91-5	(marine water)			
Reaction mass of pentamethyl-4-	Soil		0,21 mg/kg	
piperidylsebacates				
1065336-91-5	D. L.			
Reaction mass of pentamethyl-4- piperidylsebacates	Predator			no potential for bioaccumulation
1065336-91-5				
2,6-Di-tert-butyl-p-cresol	aqua	0,000199		
128-37-0 2,6-Di-tert-butyl-p-cresol	(freshwater) aqua (marine	mg/l 0,00002		
128-37-0	water)	mg/l		
2,6-Di-tert-butyl-p-cresol	sewage	0,17 mg/l		
128-37-0	treatment plant			
2,6-Di-tert-butyl-p-cresol	(STP) sediment		0,0996	
128-37-0	(freshwater)		mg/kg	
2,6-Di-tert-butyl-p-cresol	sediment		0,00996	
128-37-0 2,6-Di-tert-butyl-p-cresol	(marine water)		mg/kg	
2,6-D1-tert-butyl-p-cresol 128-37-0	Soil		0,04769 mg/kg	
2,6-Di-tert-butyl-p-cresol	oral		8,33 mg/kg	
128-37-0				
2,6-Di-tert-butyl-p-cresol	aqua (intermittent	0,00199		
128-37-0	(intermittent releases)	mg/l		
2,6-Di-tert-butyl-p-cresol	Air			no hazard identified
128-37-0	<u> </u>			
methacrylic acid 79-41-4	aqua (freshwater)	0,82 mg/l		
methacrylic acid	aqua (marine	0,82 mg/l		
79-41-4	water)			
methacrylic acid	sewage	10 mg/l		
79-41-4	treatment plant (STP)			
methacrylic acid	aqua	0,82 mg/l		
		0,02 mg/1	I	

79-41-4	(intermittent releases)			
methacrylic acid 79-41-4	Soil		1,2 mg/kg	
Ethylene dimethacrylate 97-90-5	aqua (freshwater)	0,139 mg/l		
Ethylene dimethacrylate 97-90-5	aqua (marine water)	0,0139 mg/l		
Ethylene dimethacrylate 97-90-5	aqua (intermittent releases)	0,15 mg/l		
Ethylene dimethacrylate 97-90-5	sewage treatment plant (STP)	57 mg/l		
Ethylene dimethacrylate 97-90-5	sediment (freshwater)		1,6 mg/kg	
Ethylene dimethacrylate 97-90-5	sediment (marine water)		0,16 mg/kg	
Ethylene dimethacrylate 97-90-5	Air			no hazard identified
Ethylene dimethacrylate 97-90-5	Soil		0,239 mg/kg	
Ethylene dimethacrylate 97-90-5	Predator			no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	aqua (freshwater)	0,001 mg/l		
Isobornyl acrylate 5888-33-5	aqua (intermittent releases)	0,007 mg/l		
Isobornyl acrylate	aqua (marine	0,0001		
5888-33-5	water)	mg/l		
Isobornyl acrylate 5888-33-5	sewage treatment plant (STP)	2 mg/l		
Isobornyl acrylate 5888-33-5	sediment (freshwater)		0,145	
Isobornyl acrylate	(freshwater) sediment		mg/kg 0.0145	
5888-33-5	(marine water)		0,0145 mg/kg	
Isobornyl acrylate 5888-33-5	Soil		0,0285 mg/kg	
Isobornyl acrylate 5888-33-5	Predator		00	no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2-Hydroxyethyl methacrylate 868-77-9	Workers	dermal	Long term exposure - systemic effects		1,3 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Workers	Inhalation	Long term exposure - systemic effects		4,9 mg/m3	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	Inhalation	Long term exposure - systemic effects		2,9 mg/m3	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	Workers	Inhalation	Long term exposure - systemic effects		21 mg/m3	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	Workers	dermal	Long term exposure - systemic effects		3 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	General population	inhalation	Long term exposure - systemic effects		5,2 mg/m3	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	General population	dermal	Long term exposure - systemic effects		1,5 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	General population	oral	Long term exposure - systemic effects		1,5 mg/kg	
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	Workers	inhalation	Long term exposure - systemic effects		7,4 mg/m3	
Glycerol, propoxylated, esters with acrylic acid 1-6.5PO 52408-84-1	Workers	dermal	Long term exposure - systemic effects		2,1 mg/kg	
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Workers	inhalation	Long term exposure - systemic effects		1,27 mg/m3	no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Workers	dermal	Long term exposure - systemic effects		1,8 mg/kg	no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	General population	dermal	Long term exposure - systemic effects		0,9 mg/kg	no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	General population	inhalation	Long term exposure - systemic effects		0,31 mg/m3	no potential for bioaccumulation
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	General population	oral	Long term exposure - systemic effects		0,18 mg/kg	no potential for bioaccumulation
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	inhalation	Long term exposure - systemic effects		3,5 mg/m3	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	dermal	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	inhalation	Long term exposure - systemic effects		0,86 mg/m3	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	dermal	Long term exposure - systemic effects		0,25 mg/kg	no hazard identified
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	oral	Long term exposure - systemic effects		0,25 mg/kg	no hazard identified
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - local effects		88 mg/m3	
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure -		29,6 mg/m3	

1			systemic effects		
methacrylic acid 79-41-4	Workers	dermal	Long term exposure - systemic effects	4,25 mg/kg	
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - local effects	6,55 mg/m3	
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - systemic effects	6,3 mg/m3	
methacrylic acid 79-41-4	General population	dermal	Long term exposure - systemic effects	2,55 mg/kg	
Ethylene dimethacrylate 97-90-5	Workers	inhalation	Long term exposure - systemic effects	2,45 mg/m3	no hazard identified
Ethylene dimethacrylate 97-90-5	Workers	dermal	Long term exposure - systemic effects	1,3 mg/kg	no hazard identified
Ethylene dimethacrylate 97-90-5	General population	inhalation	Long term exposure - systemic effects	1,45 mg/m3	no hazard identified
Ethylene dimethacrylate 97-90-5	General population	dermal	Long term exposure - systemic effects	0,83 mg/kg	no hazard identified
Ethylene dimethacrylate 97-90-5	General population	oral	Long term exposure - systemic effects	0,83 mg/kg	no hazard identified
Isobornyl acrylate 5888-33-5	Workers	dermal	Long term exposure - systemic effects	1,39 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	oral	Long term exposure - systemic effects	0,83 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - systemic effects	0,83 mg/kg	no potential for bioaccumulation

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	black
Odor	Acrylic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	< 0 °C (< 32 °F)
Initial boiling point	>149 °C (>300.2 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	> 93 °C (> 199.4 °F)
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (40 °C (104 °F);)	> 20,5 mm2/s
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	practically insoluble
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	< 1,3 kPa
(20 °C (68 °F))	y
Density	1,10 - 1,20 g/cm3 no method / method unknown
(20 °C (68 °F))	
Relative vapour density: (20 °C)	> 1
Particle characteristics	Not applicable
	Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity Reacts with strong oxidants. Acids. Reducing agents. Strong bases.

10.2. Chemical stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides. Hydrocarbons nitrogen oxides Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type		-	
2-Hydroxyethyl methacrylate 868-77-9	LD50	5.564 mg/kg	rat	FDA Guideline
7,7,9(or 7,9,9)-trimethyl- 4,13-dioxo-3,14-dioxa- 5,12-diazahexadecane- 1,16-diyl bismethacrylate 72869-86-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Phenyl bis(2,4,6- trimethylbenzoyl)- phosphine oxide 162881-26-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	LD50	5.564 mg/kg	rat	FDA Guideline
Triacrylate ester 52408-84-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	LD50	3.230 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Butyl hydroxytoluene 128-37-0	LD50	> 6.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
methacrylic acid 79-41-4	LD50	1.320 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Ethylene dimethacrylate 97-90-5	LD50	8.700 mg/kg	rat	FDA Guideline
Isobornyl acrylate 5888-33-5	LD50	4.350 mg/kg	rat	not specified

Acute dermal toxicity:

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
2-Hydroxyethyl methacrylate 868-77-9	LD50	> 5.000 mg/kg	rabbit	not specified
7,7,9(or 7,9,9)-trimethyl- 4,13-dioxo-3,14-dioxa- 5,12-diazahexadecane- 1,16-diyl bismethacrylate 72869-86-4	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Phenyl bis(2,4,6- trimethylbenzoyl)- phosphine oxide 162881-26-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	LD50	> 5.000 mg/kg	rabbit	not specified
Triacrylate ester 52408-84-1	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	LD50	> 3.170 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	Acute toxicity estimate (ATE)	3.171 mg/kg		Expert judgement
Butyl hydroxytoluene 128-37-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
methacrylic acid 79-41-4	LD50	500 - 1.000 mg/kg	rabbit	Dermal Toxicity Screening
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	500 mg/kg		Expert judgement
Ethylene dimethacrylate 97-90-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Isobornyl acrylate 5888-33-5	LD50	> 3.000 mg/kg	rabbit	not specified

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
methacrylic acid	LC50	> 3,6 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
79-41-4						Inhalation Toxicity)
methacrylic acid	Acute	3,61 mg/l	dust/mist			Expert judgement
79-41-4	toxicity	-				
	estimate					
	(ATE)					

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
2-Hydroxyethyl	slightly	24 h	rabbit	Draize Test
methacrylate	irritating			
868-77-9				
7,7,9(or 7,9,9)-trimethyl-	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,13-dioxo-3,14-dioxa-				
5,12-diazahexadecane-				
1,16-diyl bismethacrylate				
72869-86-4				
2-Propenoic acid, 2-	not irritating	24 h	rabbit	Draize Test
methyl-, 2-(2-				
hydroxyethoxy)ethyl ester				
2351-43-1				
Triacrylate ester	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
52408-84-1				
Butyl hydroxytoluene	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
128-37-0				
methacrylic acid	corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
79-41-4				
Ethylene dimethacrylate	not irritating	24 h	rabbit	FDA Guideline
97-90-5				
Isobornyl acrylate	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
5888-33-5				

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	Category 2B (mildly irritating to eyes)		rabbit	Draize Test
7,7,9(or 7,9,9)-trimethyl- 4,13-dioxo-3,14-dioxa- 5,12-diazahexadecane- 1,16-diyl bismethacrylate 72869-86-4	not irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	irritating		rabbit	Draize Test
Triacrylate ester 52408-84-1	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Butyl hydroxytoluene 128-37-0	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
methacrylic acid 79-41-4	corrosive		rabbit	Draize Test
Ethylene dimethacrylate 97-90-5	not irritating		rabbit	Draize Test

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	not sensitising	Buehler test	guinea pig	Buehler test
2-Hydroxyethyl methacrylate 868-77-9	sensitising	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method
7,7,9(or 7,9,9)-trimethyl- 4,13-dioxo-3,14-dioxa- 5,12-diazahexadecane- 1,16-diyl bismethacrylate 72869-86-4	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Triacrylate ester 52408-84-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Butyl hydroxytoluene 128-37-0	not sensitising	Draize Test	guinea pig	Draize Test
methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Ethylene dimethacrylate 97-90-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Isobornyl acrylate 5888-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of administration	activation / Exposure time		
2-Hydroxyethyl	negative	bacterial reverse	with and without		OECD Guideline 471
methacrylate		mutation assay (e.g			(Bacterial Reverse Mutation
868-77-9		Ames test)			Assay)
2-Hydroxyethyl	positive	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
methacrylate		chromosome			Mammalian Chromosome
868-77-9		aberration test	1.1 1 1.1 .		Aberration Test)
2-Hydroxyethyl	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene
methacrylate 868-77-9		gene mutation assay			Mutation Test)
Triacrylate ester	negative	bacterial reverse	with and without		OECD Guideline 471
52408-84-1	negative	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
02100 01 1		Ames test)			Assay)
Triacrylate ester	negative	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
52408-84-1	-	chromosome			Mammalian Chromosome
		aberration test			Aberration Test)
Triacrylate ester	positive	mammalian cell	with and without		OECD Guideline 476 (In vitro
52408-84-1		gene mutation assay			Mammalian Cell Gene
D 11 1 1		1			Mutation Test)
Butyl hydroxytoluene 128-37-0	negative	bacterial reverse	with and without		not specified
128-37-0		mutation assay (e.g Ames test)			
Butyl hydroxytoluene	negative	in vitro mammalian	with and without		not specified
128-37-0	negative	chromosome	with and without		not specifica
120 57 0		aberration test			
Butyl hydroxytoluene	negative	mammalian cell	with		not specified
128-37-0	U	gene mutation assay			L
methacrylic acid	negative	bacterial reverse	with and without		equivalent or similar to OECD
79-41-4		mutation assay (e.g			Guideline 471 (Bacterial
		Ames test)			Reverse Mutation Assay)
Ethylene dimethacrylate	positive		without		OECD Guideline 473 (In vitro
97-90-5					Mammalian Chromosome
Isobornyl acrylate	nagativa	bacterial reverse	with and without		Aberration Test) OECD Guideline 471
5888-33-5	negative	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
5000-55-5		Ames test)			Assay)
Isobornyl acrylate	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
5888-33-5		gene mutation assay			Mammalian Cell Gene
					Mutation Test)
Isobornyl acrylate	negative	in vitro mammalian	with and without		OECD Guideline 487 (In vitro
5888-33-5		cell micronucleus			Mammalian Cell
		test			Micronucleus Test)
2-Hydroxyethyl	negative	oral: gavage		rat	OECD Guideline 474
methacrylate 868-77-9					(Mammalian Erythrocyte Micronucleus Test)
2-Hydroxyethyl	negative	oral: gavage		Drosophila	not specified
methacrylate	negative	orai. gavage		melanogaster	not specified
868-77-9				menunoguster	
Triacrylate ester	negative	oral: gavage		mouse	OECD Guideline 474
52408-84-1		6			(Mammalian Erythrocyte
					Micronucleus Test)
Butyl hydroxytoluene	negative	oral: feed		rat	not specified
128-37-0					
methacrylic acid 79-41-4	negative	inhalation		mouse	equivalent or similar to OECD Guideline 478 (Genetic
17-41-4					Toxicology: Rodent Dominant
					Lethal Test)
methacrylic acid	negative	oral: gavage		mouse	equivalent or similar to OECD
79-41-4		0 "B"			Guideline 474 (Mammalian
					Erythrocyte Micronucleus
					Test)
Ethylene dimethacrylate	negative	oral: unspecified		mouse	OECD Guideline 474
97-90-5					(Mammalian Erythrocyte
	1		1	1	Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2-Hydroxyethyl methacrylate 868-77-9	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
2-Hydroxyethyl methacrylate 868-77-9	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	male	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
Butyl hydroxytoluene 128-37-0		oral: feed	2 y daily	rat	male	
methacrylic acid 79-41-4	not carcinogenic	inhalation	2 y	mouse	male/female	OECD Guideline 451 (Carcinogenicity Studies)
Ethylene dimethacrylate 97-90-5		inhalation	2 years 6 hours/day, 5 days/week	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	screening	oral: gavage	rat	equivalent or similar to OECD Guideline 422 (Combined Repeated Dose Toxicity Study)
Triacrylate ester 52408-84-1	NOAEL P 750 mg/kg NOAEL F1 >= 750 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	NOAEL P < 221 mg/kg NOAEL F1 221 mg/kg		oral: feed	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butyl hydroxytoluene 128-37-0	NOAEL P 500 mg/kg	Two generation study	oral: feed	rat	not specified
methacrylic acid 79-41-4	NOAEL P 50 mg/kg NOAEL F1 400 mg/kg NOAEL F2 400 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Ethylene dimethacrylate 97-90-5	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg		oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Isobornyl acrylate 5888-33-5	NOAEL P 100 mg/kg NOAEL F1 100 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	NOAEL 100 mg/kg	oral: gavage	49 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL 0,352 mg/l	inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Triacrylate ester 52408-84-1	NOAEL 250 mg/kg	oral: gavage	28-52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butyl hydroxytoluene 128-37-0	NOAEL 25 mg/kg	oral: feed	daily	rat	not specified
methacrylic acid 79-41-4		inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Ethylene dimethacrylate 97-90-5	NOAEL 100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Isobornyl acrylate 5888-33-5	NOAEL 100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		-	-	
2-Hydroxyethyl methacrylate	LC50	> 100 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish,
868-77-9					Acute Toxicity Test)
7,7,9(or 7,9,9)-trimethyl-4,13-	LC50	10,1 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
dioxo-3,14-dioxa-5,12-					Acute Toxicity Test)
diazahexadecane-1,16-diyl					
bismethacrylate					
72869-86-4					
Phenyl bis(2,4,6-	LC50	Toxicity > Water	96 h	Danio rerio	OECD Guideline 203 (Fish,
trimethylbenzoyl)-phosphine		solubility'			Acute Toxicity Test)
oxide					
162881-26-7					
Triacrylate ester	LC50	5,74 mg/l	96 h	Danio rerio (reported as	OECD Guideline 203 (Fish,
52408-84-1				Brachydanio rerio)	Acute Toxicity Test)
Reaction mass of	LC50	0,9 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
pentamethyl-4-					Acute Toxicity Test)
piperidylsebacates					
1065336-91-5	1.070		0.61		
Butyl hydroxytoluene	LC50	Toxicity > Water	96 h	Brachydanio rerio (new name:	EU Method C.1 (Acute
128-37-0		solubility		Danio rerio)	Toxicity for Fish)
Butyl hydroxytoluene	NOEC	0,053 mg/l	30 d	Oryzias latipes	OECD Guideline 210 (fish
128-37-0				~	early lite stage toxicity test)
methacrylic acid	LC50	85 mg/l	96 h	Salmo gairdneri (new name:	EPA OTS 797.1400 (Fish
79-41-4				Oncorhynchus mykiss)	Acute Toxicity Test)
Ethylene dimethacrylate	LC50	15,95 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
97-90-5					Acute Toxicity Test)
Isobornyl acrylate	LC50	0,704 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
5888-33-5					Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2-Hydroxyethyl methacrylate	EC50	380 mg/l	48 h	Daphnia magna	OECD Guideline 202
868-77-9					(Daphnia sp. Acute
			10.1		Immobilisation Test)
7,7,9(or 7,9,9)-trimethyl-4,13-	EC50	> 1,2 mg/l	48 h	Daphnia magna	OECD Guideline 202
dioxo-3,14-dioxa-5,12-					(Daphnia sp. Acute
diazahexadecane-1,16-diyl					Immobilisation Test)
bismethacrylate					
72869-86-4					
Phenyl bis(2,4,6-	EC50	Toxicity > Water	48 h	Daphnia magna	OECD Guideline 202
trimethylbenzoyl)-phosphine		solubility			(Daphnia sp. Acute
oxide					Immobilisation Test)
162881-26-7					
Triacrylate ester	EC50	91,4 mg/l	48 h	Daphnia magna	OECD Guideline 202
52408-84-1					(Daphnia sp. Acute
					Immobilisation Test)
Butyl hydroxytoluene	EC50	0,48 mg/l	48 h	Daphnia magna	OECD Guideline 202
128-37-0					(Daphnia sp. Acute
					Immobilisation Test)
methacrylic acid	EC50	> 130 mg/l	48 h	Daphnia magna	EPA OTS 797.1300
79-41-4					(Aquatic Invertebrate Acute
					Toxicity Test, Freshwater

			1		Daphnids)
Ethylene dimethacrylate	EC50	44,9 mg/l	48 h	Daphnia magna	OECD Guideline 202
97-90-5					(Daphnia sp. Acute
					Immobilisation Test)
Isobornyl acrylate	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202
5888-33-5					(Daphnia sp. Acute
					Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
2-Hydroxyethyl methacrylate 868-77-9	NOEC	24,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	NOEC	Toxicity > Water solubility	21 day	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	NOEC	1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Butyl hydroxytoluene 128-37-0	NOEC	0,069 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Ethylene dimethacrylate 97-90-5	NOEC	5,05 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Isobornyl acrylate 5888-33-5	NOEC	0,092 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	EC50	836 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	,
2-Hydroxyethyl methacrylate 868-77-9	NOEC	400 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
7,7,9(or 7,9,9)-trimethyl-4,13- dioxo-3,14-dioxa-5,12- diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	NOEC	0,21 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	EC50	Toxicity > Water solubility	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	NOEC	Toxicity > Water solubility	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triacrylate ester 52408-84-1	EC50	12,2 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triacrylate ester 52408-84-1	EC10	2,06 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	NOEC	0,22 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	EC50	1,68 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butyl hydroxytoluene 128-37-0	EC50	Toxicity > Water solubility	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Butyl hydroxytoluene 128-37-0	EC10	0,4 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
methacrylic acid 79-41-4	NOEC	8,2 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	EC50	45 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethylene dimethacrylate 97-90-5	EC50	17,3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethylene dimethacrylate 97-90-5	EC10	6,93 mg/l	72 h	_	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	NOEC	0,405 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	EC50	1,98 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2-Hydroxyethyl methacrylate 868-77-9	EC0	> 3.000 mg/l	16 h	Pseudomonas fluorescens	other guideline:
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	EC 50	> 100 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Triacrylate ester 52408-84-1	EC20	507 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Reaction mass of pentamethyl- 4-piperidylsebacates	IC50	100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge,

1065336-91-5					Respiration Inhibition Test)
Butyl hydroxytoluene 128-37-0	EC50	Toxicity > Water solubility	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
methacrylic acid 79-41-4	EC10	100 mg/l	17 h		not specified
Ethylene dimethacrylate 97-90-5	EC50	570 mg/l	3 h	activated sludge of a predominantly domestic sewa	ISO 8192 (Test for ge Inhibition of Oxygen Consumption by Activated Sludge)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
7,7,9(or 7,9,9)-trimethyl-4,13- dioxo-3,14-dioxa-5,12- diazahexadecane-1,16-diyl bismethacrylate 72869-86-4	not readily biodegradable.	aerobic	22 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	not readily biodegradable.	aerobic	1 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2-Propenoic acid, 2-methyl-, 2-(2-hydroxyethoxy)ethyl ester 2351-43-1	readily biodegradable	aerobic	92 - 100 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Triacrylate ester 52408-84-1	readily biodegradable	aerobic	72 - 85 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Reaction mass of pentamethyl- 4-piperidylsebacates 1065336-91-5	not readily biodegradable.	aerobic	38 %	28 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Butyl hydroxytoluene 128-37-0	not readily biodegradable.	aerobic	4,5 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Butyl hydroxytoluene 128-37-0	not inherently biodegradable	aerobic	5,2 - 5,6 %	35 d	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	14 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Ethylene dimethacrylate 97-90-5	not readily biodegradable.	aerobic	69 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Isobornyl acrylate 5888-33-5	inherently biodegradable	aerobic	73,9 %	60 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Isobornyl acrylate 5888-33-5	not readily biodegradable.	aerobic	57 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	< 5				OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
Reaction mass of pentamethyl-4- piperidylsebacates 1065336-91-5	< 31,4	56 d	24,5 °C	Cyprinus carpio	other guideline:
Butyl hydroxytoluene 128-37-0	330 - 1.800	56 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
Isobornyl acrylate 5888-33-5	37	56 h	24 °C	Danio rerio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
2-Hydroxyethyl methacrylate	0,42	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
868-77-9			Flask Method)
7,7,9(or 7,9,9)-trimethyl-4,13-	3,39	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
dioxo-3,14-dioxa-5,12-			Method)
diazahexadecane-1,16-diyl			
bismethacrylate			
72869-86-4			
Phenyl bis(2,4,6-	5,8		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
trimethylbenzoyl)-phosphine			Method)
oxide			
162881-26-7			
Reaction mass of	> 2,37 - 2,77	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
pentamethyl-4-			Flask Method)
piperidylsebacates			
1065336-91-5			
Butyl hydroxytoluene	5,1		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
128-37-0			Flask Method)
methacrylic acid	0,93	22 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
79-41-4			Flask Method)
Ethylene dimethacrylate	2,4		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
97-90-5			Method)
Isobornyl acrylate	4,52		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
5888-33-5			Method)

The table below presents the data of the classified substances present in the mixture.

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
2-Hydroxyethyl methacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
868-77-9	Bioaccumulative (vPvB) criteria.
7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
5,12-diazahexadecane-1,16-diyl bismethacrylate	Bioaccumulative (vPvB) criteria.
72869-86-4	
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
oxide	Bioaccumulative (vPvB) criteria.
162881-26-7	
Triacrylate ester	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
52408-84-1	Bioaccumulative (vPvB) criteria.
Reaction mass of pentamethyl-4-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
piperidylsebacates	Bioaccumulative (vPvB) criteria.
1065336-91-5	
Butyl hydroxytoluene	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
128-37-0	Bioaccumulative (vPvB) criteria.
methacrylic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
79-41-4	Bioaccumulative (vPvB) criteria.
Ethylene dimethacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
97-90-5	Bioaccumulative (vPvB) criteria.
Isobornyl acrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
5888-33-5	Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

Product disposal:

Do not empty into drains / surface water / ground water. Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14.1.

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

UN numbe	UN number or ID number				
ADR	3082				
RID	3082				
ADN	3082				
IMDG	3082				

3082

14.2. UN proper shipping name

IATA

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Urethane dimethacrylate)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Urethane dimethacrylate)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Urethane dimethacrylate)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Urethane dimethacrylate)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Urethane dimethacrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID ADN	
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR not applicable

Tunnelcode:
not applicable
not applicable
not applicable
not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):		
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):		
Persistent organic pollutants (Regulation (EU) 2019/1021):		
VOC content	< 3 %	
(2010/75/EC)		

Not applicable Not applicable Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows: H302 Harmful if swallowed. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H361f Suspected of damaging fertility. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

Annex - Exposure Scenarios:

Exposure Scenarios for 2-Hydroxyethyl methacrylate can be downloaded under the following link: https://mysds.henkel.com/index.html#/appSelection