



## Liqcreate - Strong-X

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Liqcreate - Strong-X  
**Other means of identification:**  
**UFI:** NERY-E0JV-M00Q-HJX4
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
 Relevant uses: Resin for 3D Printing. For professional users/industrial user only.  
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
 ALT Group BV  
 Texasdreef 7  
 3565 CL Utrecht - The Netherlands  
 Phone: +31850605849  
 info@liqcreate.com  
 www.liqcreate.com
- 1.4 Emergency telephone number:** +31850605849 Mo-Fr 8:30-17:00

### SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411  
 Eye Irrit. 2: Eye irritation, Category 2, H319  
 Skin Irrit. 2: Skin irritation, Category 2, H315  
 Skin Sens. 1B: Sensitisation, skin, Category 1B, H317
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Warning**
- 

- Hazard statements:**  
 Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
 Eye Irrit. 2: H319 - Causes serious eye irritation.  
 Skin Irrit. 2: H315 - Causes skin irritation.  
 Skin Sens. 1B: H317 - May cause an allergic skin reaction.
- Precautionary statements:**  
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P264: Wash thoroughly after handling.  
 P272: Contaminated work clothing should not be allowed out of the workplace.  
 P273: Avoid release to the environment.  
 P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.  
 P302+P352: IF ON SKIN: Wash with plenty of water.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P332+P313: If skin irritation occurs: Get medical advice/attention.  
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313: If eye irritation persists: Get medical advice/attention.  
 P391: Collect spillage.  
 P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
- Supplementary information:**  
 Contains (octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate, Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide, pentaerythritol tetraacrylate.  
**UFI:** NERY-E0JV-M00Q-HJX4

- CONTINUED ON NEXT PAGE -

**Liqcreate - Strong-X**

**SECTION 2: HAZARDS IDENTIFICATION (continued)**

**Additional labeling:**

UFI: NERY-E0JV-M00Q-HJX4

**2.3 Other hazards:**

Product fails to meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product fails to meet the criteria.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**







Non-applicable

**3.2 Mixture:**

**Chemical description:** Mixture of substances

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 42594-17-2 EC: 255-901-3 Index: Non-applicable REACH: 01-2120051112-76-XXXX	<b>(octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate<sup>(1)</sup></b> Self-classified Regulation 1272/2008 Aquatic Chronic 2: H411; Skin Sens. 1B: H317 - Warning 	40 - <65 %
CAS: 41637-38-1 EC: 609-946-4 Index: Non-applicable REACH: 01-2119980659-17-XXXX	<b>Esterification products of 4,4'-isopropylidenediphenol, ethoxylated and 2-methylprop-2-enoic acid<sup>(1)</sup></b> Self-classified Regulation 1272/2008 Aquatic Chronic 4: H413	9 - <30 %
CAS: 4986-89-4 EC: 225-644-1 Index: 607-122-00-9 REACH: Non-applicable	<b>pentaerythritol tetraacrylate<sup>(1)</sup></b> ATP CLP00 Regulation 1272/2008 Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning 	9 - <30 %
CAS: 75980-60-8 EC: 278-355-8 Index: 015-203-00-X REACH: 01-2119972295-29-XXXX	<b>Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide<sup>(1)</sup></b> Self-classified Regulation 1272/2008 Aquatic Chronic 2: H411; Repr. 2: H361f; Skin Sens. 1B: H317 - Warning 	0,5 - <2 %
CAS: 110-82-7 EC: 203-806-2 Index: 601-017-00-1 REACH: 01-2119463273-41-XXXX	<b>cyclohexane<sup>(2)</sup></b> ATP CLP00 Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger 	0,01 - <0,1 %
CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX	<b>Toluene<sup>(2)</sup></b> ATP CLP00 Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger 	0,01 - <0,1 %
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	<b>N-butyl acetate<sup>(2)</sup></b> ATP CLP00 Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning 	<0,01 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

- CONTINUED ON NEXT PAGE -

**Liqcreate - Strong-X****SECTION 4: FIRST AID MEASURES (continued)****By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:****Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

See section 8.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

- CONTINUED ON NEXT PAGE -

## Liqcreate - Strong-X

### SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

#### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and destroy using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

#### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 15 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	200 ppm	700 mg/m <sup>3</sup>
cyclohexane CAS: 110-82-7 EC: 203-806-2	IOELV (STEL)		
	IOELV (8h)	50 ppm	192 mg/m <sup>3</sup>
Toluene CAS: 108-88-3 EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m <sup>3</sup>
	IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>

#### DNEL (Workers):

- CONTINUED ON NEXT PAGE -

**Liqcreate - Strong-X**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Esterification products of 4,4'-isopropylidenediphenol, ethoxylated and 2-methylprop-2-enoic acid CAS: 41637-38-1 EC: 609-946-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	3,52 mg/m <sup>3</sup>	Non-applicable
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide CAS: 75980-60-8 EC: 278-355-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,233 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,822 mg/m <sup>3</sup>	Non-applicable
cyclohexane CAS: 110-82-7 EC: 203-806-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2016 mg/kg	Non-applicable
	Inhalation	1400 mg/m <sup>3</sup>	1400 mg/m <sup>3</sup>	700 mg/m <sup>3</sup>	700 mg/m <sup>3</sup>
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
	Inhalation	384 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	600 mg/m <sup>3</sup>	600 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Esterification products of 4,4'-isopropylidenediphenol, ethoxylated and 2-methylprop-2-enoic acid CAS: 41637-38-1 EC: 609-946-4	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,87 mg/m <sup>3</sup>	Non-applicable
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide CAS: 75980-60-8 EC: 278-355-8	Oral	Non-applicable	Non-applicable	0,0833 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,0833 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,145 mg/m <sup>3</sup>	Non-applicable
cyclohexane CAS: 110-82-7 EC: 203-806-2	Oral	Non-applicable	Non-applicable	59,4 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1186 mg/kg	Non-applicable
	Inhalation	412 mg/m <sup>3</sup>	412 mg/m <sup>3</sup>	206 mg/m <sup>3</sup>	206 mg/m <sup>3</sup>
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
	Inhalation	226 mg/m <sup>3</sup>	226 mg/m <sup>3</sup>	56,5 mg/m <sup>3</sup>	56,5 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>

**PNEC:**

Identification					
(octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate CAS: 42594-17-2 EC: 255-901-3	STP	10 mg/L	Fresh water	0,0016 mg/L	
	Soil	0,131 mg/kg	Marine water	0,00016 mg/L	
	Intermittent	0,016 mg/L	Sediment (Fresh water)	0,658 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,066 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide CAS: 75980-60-8 EC: 278-355-8	STP	Non-applicable	Fresh water	0,0014 mg/L	
	Soil	0,0222 mg/kg	Marine water	0,00014 mg/L	
	Intermittent	0,014 mg/L	Sediment (Fresh water)	0,115 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,0115 mg/kg	
cyclohexane CAS: 110-82-7 EC: 203-806-2	STP	3,24 mg/L	Fresh water	0,207 mg/L	
	Soil	3,38 mg/kg	Marine water	0,207 mg/L	
	Intermittent	0,207 mg/L	Sediment (Fresh water)	16,68 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	16,68 mg/kg	

- CONTINUED ON NEXT PAGE -

**Liqcreate - Strong-X**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**


Identification				
Toluene CAS: 108-88-3 EC: 203-625-9	STP	13,61 mg/L	Fresh water	0,68 mg/L
	Soil	2,89 mg/kg	Marine water	0,68 mg/L
	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,09 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg

**8.2 Exposure controls:**



**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: FFP2)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**


Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks (Material: Nitrile)			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**


Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.

- CONTINUED ON NEXT PAGE -





**Liqcreate - Strong-X**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0,06 % weight
V.O.C. density at 20 °C:	0,72 kg/m <sup>3</sup> (0,72 g/L)
Average carbon number:	6,46
Average molecular weight:	90,12 g/mol

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	 Grey
Odour:	Resin
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	Non-applicable *
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	~1120,3 kg/m <sup>3</sup>
Relative density at 20 °C:	1,12
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm <sup>2</sup> /s
Concentration:	Non-applicable *
pH:	≈6 - 8 (at 100 %)
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**Liqcreate - Strong-X**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
<b>Flammability:</b>	
Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	260 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
<b>Particle characteristics:</b>	
Median equivalent diameter:	Non-applicable

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

**Other safety characteristics:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

- CONTINUED ON NEXT PAGE -



**Liqcreate - Strong-X**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Toluene (3); Carbon black (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide CAS: 75980-60-8 EC: 278-355-8	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
cyclohexane CAS: 110-82-7 EC: 203-806-2	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

- CONTINUED ON NEXT PAGE -

**Liqcreate - Strong-X**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity		Genus
	Route	Dose	
Toluene CAS: 108-88-3 EC: 203-625-9	LD50 oral	5580 mg/kg	Rat
	LD50 dermal	12124 mg/kg	Rat
	LC50 inhalation	28,1 mg/L (4 h)	Rat
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat

**11.2 Information on other hazards:**

**Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

**Other information**

Non-applicable

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

**Acute toxicity:**

Identification	Concentration		Species	Genus
	Endpoint	Dose		
(octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate CAS: 42594-17-2 EC: 255-901-3	LC50	1,65 mg/L (96 h)	Danio rerio	Fish
	EC50	2,4 mg/L (48 h)	N/A	Crustacean
	EC50	1,2 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide CAS: 75980-60-8 EC: 278-355-8	LC50	>1 - 10 (96 h)		Fish
	EC50	>1 - 10 (48 h)		Crustacean
	EC50	>1 - 10 (72 h)		Algae
cyclohexane CAS: 110-82-7 EC: 203-806-2	LC50	>0.1 - 1 (96 h)		Fish
	EC50	>0.1 - 1 (48 h)		Crustacean
	EC50	>0.1 - 1 (72 h)		Algae
Toluene CAS: 108-88-3 EC: 203-625-9	LC50	5,5 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50	3,78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	Non-applicable		
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	Non-applicable		
	EC50	Non-applicable		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae

**Chronic toxicity:**

**Liqcreate - Strong-X**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Concentration		Species	Genus
	NOEC	Non-applicable		
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
cyclohexane CAS: 110-82-7 EC: 203-806-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
Toluene CAS: 108-88-3 EC: 203-625-9	BOD5	2,5 g O2/g	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	Non-applicable	% Biodegradable	84 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
cyclohexane CAS: 110-82-7 EC: 203-806-2	BCF	66
	Pow Log	3.44
	Potential	Moderate
Toluene CAS: 108-88-3 EC: 203-625-9	BCF	90
	Pow Log	2.73
	Potential	Moderate
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
cyclohexane CAS: 110-82-7 EC: 203-806-2	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,465E-2 N/m (25 °C)	Moist soil	Non-applicable
Toluene CAS: 108-88-3 EC: 203-625-9	Koc	178	Henry	672,8 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable

- CONTINUED ON NEXT PAGE -

**Liqcreate - Strong-X**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product fails to meet the criteria.

**12.7 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Other information:**

ADR/RID: Special Provisions 274, 335, 601, 375. Not restricted as per Special Provisions 375. The provided packaging meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG: Special Provisions 274, 335, 969. Not restricted as per 2.10.2.7. The provided packaging meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA: Special Provisions A97, A158, A197. Not restricted as per Special Provisions A197. The provided packaging meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Products are transported on behalf of Liqcreate in sizes ≤5 L or ≤5 kg. The environmentally hazardous substance mark & the marine pollutant mark are not required when transported in sizes of ≤5 L or ≤5 kg.

**Transport of dangerous goods by land:**

With regard to ADR 2021 and RID 2021:

**Liqcreate - Strong-X**

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate
- 14.3 Transport hazard class(es):** 9  
Labels: 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**  
Special regulations: 274, 335, 375, 601  
Tunnel restriction code: -  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate
- 14.3 Transport hazard class(es):** 9  
Labels: 9
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**  
Special regulations: 335, 969, 274  
EmS Codes: F-A, S-F  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2022:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate
- 14.3 Transport hazard class(es):** 9  
Labels: 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable  
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

- CONTINUED ON NEXT PAGE -

**Liqcreate - Strong-X**

**SECTION 15: REGULATORY INFORMATION (continued)**

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200	500

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
  - tricks and jokes,
  - games for one or more participants, or any article intended to be used as such, even with ornamental aspects.
- Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

COMMISSION REGULATION (EU) 2020/878

**Texts of the legislative phrases mentioned in section 2:**

- H411: Toxic to aquatic life with long lasting effects.
- H317: May cause an allergic skin reaction.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

- Aquatic Acute 1: H400 - Very toxic to aquatic life.
- Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
- Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life.
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
- Eye Irrit. 2: H319 - Causes serious eye irritation.
- Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
- Flam. Liq. 3: H226 - Flammable liquid and vapour.
- Repr. 2: H361d - Suspected of damaging the unborn child.
- Repr. 2: H361f - Suspected of damaging fertility.
- Skin Irrit. 2: H315 - Causes skin irritation.
- Skin Sens. 1: H317 - May cause an allergic skin reaction.
- Skin Sens. 1B: H317 - May cause an allergic skin reaction.
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
- STOT SE 3: H336 - May cause drowsiness or dizziness.

**Classification procedure:**

- CONTINUED ON NEXT PAGE -

**Liqcreate - Strong-X****SECTION 16: OTHER INFORMATION (continued)**

Aquatic Chronic 2: Calculation method

Skin Sens. 1B: Calculation method

Skin Irrit. 2: Calculation method

Eye Irrit. 2: Calculation method

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50


LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

LIQCREATE



The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -