

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** REFLECON® tarnish-12 (Aerosol)
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Life cycle stages**
  - F Formulation or re-packing
  - IS Use at industrial Sites
- **Sector of Use**
  - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC14 Metal surface treatment products
- **Process category** PROC7 Industrial spraying
- **Environmental release category** ERC7 Use of functional fluid at industrial site
- **Article category** AC7 Metal articles
- **Application of the substance / the mixture** Anti-reflection agent for optical 3D-metrology
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
  - MR Chemie GmbH
  - Nordstr. 61-63
  - 59427 Unna (Germany)
  - Tel. +49 (0)2303 95151 0
  - Fax: +49 (0)2303 95151 10
  - post@mr-chemie.de
  - www.mr-chemie.de
- **Further information obtainable from:**
  - MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de
- **1.4 Emergency telephone number:**
  - 24h- Emergency Contact Phone Number For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident (WISAG FMO Cargo Service GmbH & CO.KG)
  - Call Day or Night within USA and Canada: 1 800 424 9300
  - Outside USA and Canada: 001 703 527 3887
  - In-Country Emergency Number for:
  - Germany: 0800-181-7059
  - China: 4001 204937 (Mandarin)
  - Hong Kong: 800 968 793 (Cantonese)
  - India: 000 800 100 7141 (Hindi)
  - South Africa: 0 800 983 611 (English)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
  - **Classification according to Regulation (EC) No 1272/2008**
    - The mixture is classified according to Regulation (EC) No 1272/2008 according to the most recent ATP.
- |                   |           |  |
|-------------------|-----------|--|
| Aerosol 1         | H222-H229 | Extremely flammable aerosol. Pressurised container: May burst if heated. |
| Asp. Tox. 1       | H304      | May be fatal if swallowed and enters airways.                            |
| Aquatic Chronic 3 | H412      | Harmful to aquatic life with long lasting effects.                       |
- 
- **2.2 Label elements**
  - **Labelling according to Regulation (EC) No 1272/2008**
    - The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

Trade name: REFLECON® tarnish-12 (Aerosol)

(Contd. of page 1)

### · Hazard pictograms



GHS02 GHS08

### · Signal word Danger

### · Hazard-determining components of labelling:

pentane

### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

### · 2.3 Other hazards

### · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

### · Dangerous components:

CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-XXXX	butane (containing < 0,01 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	40 - 50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-XXXX	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	30 - 40%
CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30-XXXX	pentane Flam. Liq. 1, H224 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	≥ 10 - < 20%
CAS: 281-23-2 EINECS: 206-001-4 Reg.nr.: 01-2120041464-63-XXXX	tricyclo[3.3.1.1.3,7]decane Aquatic Acute 1, H400	5 - 10%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

**Trade name: REFLECON® tarnish-12 (Aerosol)**

(Contd. of page 2)

- **Propellant:** Propane-Butane

- **Additional information:**

Wording of the listed hazard phrases are indicated in section 16 and relate to individual raw components.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:** Not relevant - aerosol can.

- **Information for doctor:**

Grease with skin-cream to restore fat film in order to prevent skin inflammation.

- **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

- **5.3 Advice for firefighters**

- **Protective equipment:** Wear self-contained respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.

- **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

Trade name: REFLECON® tarnish-12 (Aerosol)

(Contd. of page 3)

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, e.g. electric lights. Do not pierce or burn, even after use.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

#### Information about storage in one common storage facility: Not required.

Further information about storage conditions: Protect from heat and direct sunlight.

Recommended storage temperature: 5 - 45°C, 41 - 113 °F

### 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Additional information about design of technical facilities: No further data; see section 7.

#### Ingredients with limit values that require monitoring at the workplace:

##### 106-97-8 butane (containing < 0,01 % butadiene (203-450-8))

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

##### 109-66-0 pentane

WEL	Long-term value: 1800 mg/m <sup>3</sup> , 600 ppm
-----	---

#### DNELs

##### 109-66-0 pentane

Dermal	Long-term - systemic effects, worker	432 mg/kg bw/day (worker)
Inhalative	Long-term - systemic effects, worker	3,000 mg/m <sup>3</sup> (worker)

#### DNEL (Derived No Effect Level) for the general population

##### 109-66-0 pentane

Oral	Long term - systemic effects, general population	214 mg/kg bw/day (general population)
Dermal	Long term - systemic effects, general population	214 mg/kg bw/day (general population)
Inhalative	Long term - systemic effects, general population	643 mg/m <sup>3</sup> (general population)

#### PNECs

##### 109-66-0 pentane

Aquatic compartment - freshwater	0.23 mg/L (freshwater)
Aquatic compartment - marine water	0.23 mg/L (marine water)
Aquatic compartment - water intermittent releases	0.88 mg/L (intermittent release water)
Aquatic compartment - sediment freshwater	1.2 mg/kg sed dw (sediment fresh water)
Aquatic compartment - sediment marine water	1.2 mg/kg sed dw (sediment marine water)
Terrestrial compartment - soil	0.55 mg/kg dw (soil)
Sewage treatment plant	3.6 mg/L (sewage treatment plant)

Additional information: The lists valid during the making were used as basis.

### 8.2 Exposure controls

#### Personal protective equipment:

General protective and hygienic measures: Wash hands before breaks and at the end of work.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

Trade name: REFLECON® tarnish-12 (Aerosol)

(Contd. of page 4)

- **Respiratory protection:**

For good ventilation provide, this can be achieved by local or space exhaust. If the concentration lies over the job limit values, then, a certified respirator suitable for this purpose must be used.

- **Protection of hands:**

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

For the protection against chemicals in areas with heightened risk of injury (mechanical hazard) no recommendation for a suitable glove material can be given.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

Supplier for suitable protection gloves:

ASD ArbeitsSicherheit Dortmund

Torstr. 101 - 37355 Niederorschel OT Rüdigershagen

Tel.: 02301 / 919543 - Fax: 02301 / 9453893

E-Mail: m.schnellhardt@t-online.de - <http://www.arbeitssicherheitdortmund.de>

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Aerosol

Colour: White

- **Odour:** Solvent-like

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

- **Flash point:** -80 °C  
Basis: propellant

- **Flammability (solid, gas):** Not applicable.

- **Auto-ignition temperature:** Not determined - aerosol.

- **Decomposition temperature:** Not determined.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

Trade name: REFLECON® tarnish-12 (Aerosol)

(Contd. of page 5)

· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined.
· <b>Explosion limits:</b> <b>Lower:</b> <b>Upper:</b>	1.5 Vol % 10.9 Vol %
· <b>Vapour pressure at 20 °C:</b>	8,300 hPa Basis: propellant
· <b>Density at 20 °C:</b> · <b>Relative density</b> · <b>Vapour density</b> · <b>Evaporation rate</b>	0.8 g/cm <sup>3</sup> Basis: active substance Not determined. Not determined. Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b> <b>Dynamic:</b> <b>Kinematic:</b>	Not determined. Not determined.
· <b>Solvent separation test:</b> <b>Organic solvents:</b> <b>VOC (EU)</b>	90.2 % 90.21 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
Danger of bursting of the aerosol can during overheating
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · **LD/LC50 values relevant for classification:**

**106-97-8 butane (containing < 0,01 % butadiene (203-450-8))**

Inhalative | LC50/4 h | 658 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

Trade name: REFLECON® tarnish-12 (Aerosol)

(Contd. of page 6)

- **General remarks:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste disposal key:**  
The references regarding disposal refer to the pure unchanged product.  
For this product no waste key number can be specified, because only the intended purpose permits an allocation. The waste key number is to be specified in arrangement with the regional waste disposal.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   | <p>UN1950</p>   |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul> | <p>1950 AEROSOLS<br/>AEROSOLS<br/>AEROSOLS, flammable</p> |

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

Trade name: REFLECON® tarnish-12 (Aerosol)

(Contd. of page 7)

## · 14.3 Transport hazard class(es)

## · ADR



· Class 2.1F Gases.  
· Label 2.1

## · IMDG, IATA



· Class 2.1 Gases.  
· Label 2.1

## · 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards: Not applicable.

## · 14.6 Special precautions for user

Warning: Gases.

## · Hazard identification number (Kemler code): -

## · EMS Number:

F-D,S-U

## · Stowage Code

SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2.  
For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.

## · Segregation Code

## · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

## · Transport/Additional information:

## · ADR

## · Limited quantities (LQ)

1L

## · Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

## · Transport category

2

## · Tunnel restriction code

D

## · IMDG

## · Limited quantities (LQ)

1L

## · Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

Trade name: REFLECON® tarnish-12 (Aerosol)

(Contd. of page 8)

· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1
--------------------------	-----------------------

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **VOC (EU)** 721.7 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

- **Relevant phrases**  
The wording of the listed risk phrases are those of the individual raw materials.  
H220 Extremely flammable gas.  
H224 Extremely flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.
- **Recommended restriction of use**  
Existing national and local laws concerning chemicals are to be considered.
- **Department issuing SDS:**  
MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38
- **Contact:**  
MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de
- **Abbreviations and acronyms:**  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
DNEL: Derived No-Effect Level (UK REACH)  
PNEC: Predicted No-Effect Concentration (UK REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Gas 1A: Flammable gases – Category 1A  
Aerosol 1: Aerosols – Category 1  
Press. Gas (Comp.): Gases under pressure – Compressed gas  
Flam. Liq. 1: Flammable liquids – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. on page 10)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 22.11.2023

Version number 1

Revision: 22.11.2023

**Trade name: REFLECON® tarnish-12 (Aerosol)**

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. of page 9)

· **\* Data compared to the previous version altered.**

— GB —